



### Print fine lines accurately

The tiny four picolitre droplet size of Canon's FINE inkjet nozzle technology reproduces extremely fine lines true to the original thickness and without graininess.

### Speed to satisfy the most demanding client

A revolutionary high-density print-head design with 15,360 individual nozzles ensures the ink is delivered with absolute precision, and at a speed to satisfy the most demanding client. In fact, it prints an A2 size CAD print in only 16 seconds\*.

### The perfect mix of quality and economy

Its 6-ink reactive ink system provides the perfect mix of quality and economy. The economical dye-based ink set is enhanced with a matte black pigment ink for deeper, stronger blacks in detailed prints.

### Minimal print interruption

Two matte black ink tanks ensure minimal interruption. It has both matte and photo blacks loaded, eliminating the waste of swapping blacks for different media. It switches between the two automatically.

### The choice is clear

What's more, with the option to add a roll feeding unit to the standard cassette feeding configuration, you can have both matte and gloss paper loaded at once. So if you're looking for an efficient way to produce detailed large format prints, the choice is clear.

\*Based on printing ISOSCID No. 5 in standard mode on plain paper.

## imagePROGRAF iPF510 large format printer.

The 17-inch imagePROGRAF iPF510 is the ideal large format printer for drafting and design applications where detail is critical.

### At a glance...

- Prints up to 17-inches wide
- Supports HP-GL2 & HP-RTL
- Four picolitre ink droplet size
- High-density print-head design
- Two matte black tanks for increased efficiency
- Prints an A2 CAD print in only 16 seconds\*





## imagePROGRAF iPF510 large format printer.

**Canon**  
advanced simplicity®

Model	Canon Large Format Printer imagePROGRAF iPF510
Class	17-inch
Ink Type	4-colour dye ink (BK, C, M, Y) plus 1-colour pigment ink (MBK x 2) Total: 6 ink tanks
Installation	User installation
Dimensions (WxDxH)	Main Unit: 819mm x 733mm x 317mm
With optional printer stand	819mm x 810mm x 989mm
With auto roll feed unit (option)	819mm x 810mm x 344mm
Weight	Main Unit: 39kg; With auto roll feed unit: 43kg
Printer stand	Optional
Power supply-input power	AC220-240V (50/60Hz)
Power supply-standby	1W or less
Operational environment	Temperature: 15-30°C
Humidity	10- 80% (Condensation free)
Standard Memory	192MB

<b>Detector &amp; Adjustment</b>	
Registration adjustment	Automatic/Manual
Banding adjustment	Automatic/Manual
Line length adjustment	Manual
Head slant adjustment	Automatic
Colour calibration	No
Head gap adjustment	Automatic/Manual
Non-firing detection	Yes
Non-firing compensation	Yes
Roll media remaining detection function	Yes

<b>Firmware</b>	
Printer language	imagePROGRAF Driver, HPGL2, HP-RTL
Status reply language	CPCA, SNMP-MIB (Standard MIB, Canon-MIB)
Type	Flash ROM
Update	Updated from USB, 1394, Ethernet port (Utility use)

<b>Operation Panel</b>	
Display	LCD: 16 columns x 2 rows, LED x 5, Key x 11
Displayable languages on LCD	English, French, German, Italian, Spanish, Japanese (Katakana)

<b>Interface - USB 2.0 Hi-Speed</b>	
Type	Built-in
Mode	Full/high speed (12/480Mbit/Sec respectively), bulk transfer
Connector type:	Series B (4 pins)

<b>Interface-Ethernet</b>	
Type	Built-in
Standard	IEEE 802.3 10base-T, IEEE 802.3u 100base TX/Auto-Negotiation, IEEE 802.3 x Full Duplex
Protocol	IPX/SPX (Netware 3.2(j), 4.1(j), 4.11(j), 4.2(j), 5.0(j), 5.1 (j)) SNMP (Canon-MIB), HTTP, TCP/IP, Appletalk

<b>Interface IEEE 1394</b>	
Type	Slot card type (option)
Optional	IEEE 1394-1995, P1934a (Based on draft 2.0), Half duplex, Data/Strb differential serial
Data-transfer time	100/200/400 Mbit/sec
Connector type	In compliance with IEEE 1394-1995, 6 pins. No power supply
Expansion slot	None

<b>Print Head</b>	
Model	PF-03
Type	Bubble-jet on demand
Head configuration	6 colours integrated type(6 chips per print head x 1 print head)
Resolution	2,400 x 1,200dpi
Nozzle per chip	2,560 nozzles per chip
Droplet size	4pl per colour
Head replacement	User replaceable

<b>Ink Tank</b>	
Model	PFI-102
Supply	Tubing system
Colours	(Matte Black x 2, Photo Black, Cyan, Magenta, Yellow)
Capacity	130ml
Level Detection	Detected by dot count and electrode (Empty)
Smart chip	Each ink tank equipped with EEPRO M – stores its ink level

<b>Cutter</b>	
Type	Automatic horizontal cutting (rotary cutter), independent unit
Cutter durability (cuts)	25,000 cuts for A2-size media

<b>Media Feed &amp; Output</b>	
Roll paper (auto roll feed unit option)	One roll, front-loading, front output
Cut sheet (cassette)	Front-loading, front output
Cut sheet (manual feed)	Top-feeding, front output (For thick media, front-feeding, front output)
Paper path switch	Automatic switch from roll to cassette and vice versa
Delivery direction	Face-up, front side
Max no. stacking delivered prints	Basket (1 Sheet)

<b>Media Size</b>	
Roll paper (width)	ISO (A3, A2); JIS (B4); others (8, 10, 14, 16, 17", 300 & 329mm)
Cut sheet (cassette)	ISO (A4, A3, A3+ A2); DIN (C4, C3); JIS (B4, B3), ANSI (8.5"x11", 8.5"x14", 11"x17", 13"x19", 17"x22"); ARCH (1 2"x18"); Photo (14"x17", 12"x16", 10"x12", 10"x15", 16"x20" (US photo size)
Cut sheet (man feed from top)	ISO (A4, A3, A3+, A2, B4, B3); DIN (C4, C3); JIS (B4, B3); ANSI (8.5"x11", 8.5"x14", 11"x17", 13"x19", 17"x22"); ARCH (9"x12", 12"x18"); Photo (14"x17", 12"x16", 10"x12", 10"x15", 16"x20" (US photo size) Others (13"x22")
Cut sheet (man feed from front)	ISO (A2); ANSI (17"x22"); Others (13"x22")

<b>Media Thickness</b>	
Roll	0.07-0.80mm
Cut sheet	Cassette (0.08 – 0.30 mm); Manual feed top (0.08 – 0.50 mm); Manual feed front (0.5- 1.50mm)
Max outside diameter roll paper	150.0mm
Media core size	Internal diameter of roll core: 2" / 3"

<b>Environment Certifications</b>	
ENERGY STAR (WW) RoHS directive, IT ECO Declaration (Europe), WEEE, Executive Order of the President of the United States of America	

<b>Optional</b>	
IEEE 1394 Expansion Board	EB-05
Auto Roll Feed Unit	RU-01 (incl. attachment for 3" core and borderless print spacer)
Roll holder Set	RH2-11 (incl. attachment for 3" core and borderless print spacer)
Printer Stand	ST-11
Media Basket	BU-02

<b>Consumables</b>	
Ink Tank (130ml)	PFI-102 (MBK, BK, C, M, Y)
Print Head	PF-03
Maintenance Cartridge	MC-05

©2007 Canon Australia Pty Ltd. All rights reserved. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon reserves the right to change specifications without notice.

