C9655 Specifications

OKI



High speed, high volume printer for high quality colour printing in the office

The C9655 is the perfect addition to any business. This high performance, cost-effective colour printer has the speed, volume and flexibility to handle all the day's demands with ease – be it general office printing or creative graphics work.

With this outstanding versatility comes the utmost reliability. Designed by OKI, the leaders in business printing, the C9655 incorporates technology that ensures smooth, trouble free working.

Handles multiple media.

Meets the day's demands.

- Offers outstanding media handling 64 to 300gsm weight and sizes from A6 to SRA3 and banners 1200mm long
- Broad capability enables creative in-house printing solutions whether for banners, booklets or business cards
- Up to 2,880 sheet paper input capacity high capacity trays helping to maintain workflow and minimise user involvement
- Duplex models for full-speed double-sided printing to save time, paper and operator involvement
- 3 additional paper trays on the C9655hdtn, perfect for printing large quantities in one go or setting up four different media types

 Finishing flexibility with optional saddlestitch, fold, staple or hole-punch to give documents that professional touch

Exceptional colour. High performance printing.

- Excellent A4 print speed of 36ppm colour/ 40ppm mono (19ppm colour/ 21ppm mono for A3) maximises productivity
- Graphic Pro colour management provides the tools to download colour profiles to the Hard Disk Drive for specific highly accurate colour matching
- ProQ2400 Multi-level technology and microfine High Definition toner together provide a better level of detail, greater colour depth, reduced grain and a high gloss feel
- 512MB RAM and 800MHz processor means large print jobs are processed efficiently and easily

Protect the data. Control the colour.

- Print Control imposes rules on how the printer is used
- Secure Erase can safely wipe all details of a job from the Hard Disk Drive
- Data Encryption prevents unauthorized reading of confidential data
- Password Protection allows users to retrieve confidential documents using a pin number

So simple to set up. So easy to refill.

- Informative graphical display panel simplifies every operation
- User installable consumables are easy and quick to change, thereby maintaining productivity
- Template Manager, supplied free in the box, enables the creation of professional looking documents in house
- Optional finisher for automatic hole-punching, folding, saddle stitching and booklet making

Designed to handle the workload. Built to keep working.

- Robust, award winning, digital LED technology and single-pass print technology
- Fewer moving parts means a more reliable machine
- Keeps the work flowing smoothly handling a wide range of media
- Unique Auto Media Detect feature automatically detects different media settings, saving the user from manually resetting the printer when changing paper types

| A4/A3 | ~ |
|-------------------------|-----|
| Range of media handling | ~ |
| Colour, mono | |
| Print | · · |
| | • |
| 1-30 users | ~ |

Variants available: C9655n networked C9655dn duplex, networked C9655hdtn hard disk drive, duplex, high capacity feeder, networked



C9655 - Colour and Mono Printers

| Print speed | A4: 36ppm colour, 40ppm mono; A3: 19ppm colour, 21ppm mono | | Standard RAM: 512MB; Maximum RAM: 1024MB | |
|---|--|---|---|--|
| Time to first print | 10.5 seconds colour, 9 seconds mono | Memory | Hard Disk Drive: 40GB (Optional on C9655n/C9655dn) | |
| Warm up time Processor speed | 85 seconds or less from power on PowerPC 750 800MHz | Environment | Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended | |
| | | | Storage temperature/ humidity: -20°C to 45°C, 10% to 90%RH | |
| INTERFACE AND SOFTWARE | | Power supply | Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz | |
| Connectivity | IEEE 1284 Bi-directional Parallel, Hi-Speed USB 2.0, | Power consumption | Typical: 750W; Max: 1500W; Idle: 200W; Power Save: <26W | |
| Printer languages | 10Base-T/100Base-TX/1000Base-T Ethernet PCL5c, PCLXL (colour), Adobe PostScript 3 with direct PDF | Noise level | Operating: 54dB(A) or less; Standby: 42dB(A) or less; Power save: 28dB(A) after 30 mins | |
| Network & protocols | Printing (v1.6), SIDM 10Base-T/100Base-TX/1000Base-T Ethernet Card with internal Web Server for printer and network card set-up and management. TCP/IP:- ARP, RARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, LLTD, JetDirect protocols. Netware 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. EtherTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other: EAP IPv6, 802.1x authentication, SNMPv3, SSL3/TLS HTTPS | Dimensions (HxWxD) | C9655n/C9655dn: 471 x 654.5 x 623mm; C9655hdtn: 873 x 654.5 x 623mm | |
| | | Weight ³ | C9655n: 76kg; C9655dn: 81kg; C9655hdtn: 133kg | |
| | | Duty cycle | Maximum: 150,000 pages/month; Recommended: 5,000 to 15,000 pages per month | |
| | | Warranty | 3 years extended warranty upon registration within 30 days of purchase | |
| | | Product order numbers | C9655n : 01307501; C9655dn : 01307601; C9655hdtn : 01307801 | |
| Advanced networking & security | encryption, Data Encryption ² , MAC filtering, IP filtering, Secure Erase ² , Secure Print ² | Accessories (Order Numbers) | | |
| OS Compatibility ¹ | Windows 2000 / XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 R2 / Server 2008 (32-bit & 64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit); Mac OS X (10.3,9 to 10.6.5) | 2nd/3rd paper tray | 42831303 | |
| | | 2nd/3rd lockable paper tray | 01216601 | |
| , | | Duplex | 42797203 (Standard on C9655dn/C9655hdtn) | |
| | Template Manager ³ , Color Correct, OKI LPR ³ , Color Correct Utility, Color Swatch Utility, Color Access Policy Manager ³ , PrintSuperVision.net ³ , PrintSuperVision Java ³ , Print Control Server ³ , Print Control Client, Print Control Report Tool ³ , Web Driver Installer ³ , ICC Color Profiles ³ , PostScript Gamma Utility, Profile Assistant, PDF Direct Print, Storage Device Manager ² , | High Capacity Feeder | 42831503 (Standard on C9655hdtn) | |
| Utility suite ¹ | | Cabinet | 09004256 (Not available on C9655hdtn) | |
| | | Memory | 256MB: 01182901; 512MB: 01182902 | |
| | | Hard Disk Drive | 40GB: 01163803 (Standard on C9655hdtn) | |
| | | 4-tray Finisher | 01166701 (High Capacity Feeder required) | |
| ColorSync Profiles, ICC Profiles ³ | | 5-tray Finisher | 01166801 (High Capacity Feeder & 2nd paper tray required) | |
| Paper Handling | | 2-hole Finisher-Punch Unit | 42872901 (Finisher unit required) | |
| | Tray 1: 530 sheets of 80gsm; | 4-hole Finisher-Punch Unit | 42872903 (Finisher unit required) | |
| Paper capacity | Multi-purpose tray: 230 sheets of 80gsm | 4-hole (Swedish) Finisher-Punch Unit 42872904 (Finisher unit required) | | |
| Paper capacity optional tray | Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm High Capacity Feeder: 1,590 sheets of 80gsm (standard on C9655hdtn) | Consumables (Order Numbers) | | |
| Maximum paper capacity | 2,880 sheets of 80gsm Tray 1/2/3: A3+, A3, A4, A5, A6, Custom size: Width 105 - | Toner cartridges* (22,000 pages) | Cyan: 43837131; Magenta: 43837130; Yellow: 43837129 | |
| Paper sizes | 328mm Length 148 - 457mm; Multi-purpose tray: A3+, A3, A4, A5, A6, Custom size: Width 76 - 328mm Length 127 - 1,200mm; | Toner cartridge* (22,500 pages) | Black: 43837132 | |
| | High Capacity Feeder: A3+, A3, A4, A5, A6, Custom size: Width 105 - 328mm Length 148 - 457mm Tray 1/2/3: 64 to 216gsm: Multi-purpose tray: 64 to 300gsm; | Image drum** (30,000 pages) | Cyan: 42918107; Magenta: 42918106; Yellow: 42918105; Black: 42918108 | |
| Paper weight Duplex | Duplex: 64 to 188gsm; High Capacity Feeder: 64 to 216gsm | Transfer Belt (100,000 pages) | 42931603 | |
| Paper output | | Fuser Unit (100,000 pages) | 42931703 | |
| Рарегоцири | 500 sheets face down tray, 200 sheets face up tray | Waste Toner Box (30,000 pages) | 42869403 | |
| Printer fonts | 86 scalable PCL fonts, 1 bitmap font, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts | Finisher Staples (15,000 staples) | 42937603 | |
| Barcode | · · · · | | | |
| | | *Toners: A4 pages yield comp pages yield compliant with IS | liant with ISO/ISC 19798. Printer shipped with toner for 7,500 A4 D/ISC 19798. | |
| PRINT QUALITY | · · · · · · · · · · · · · · · · · · · | **Drum: Average number of A | | |
| Resolution | ProQ2400 Multi-level technology, 1200 x 600dpi | | | |

¹Check local OKI website for latest driver releases and OS compatibility; ²Hard Disk Drive required; ³Windows only; ⁴Including all consumables.

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.

3 Year On-Site Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit: **www.okl.co.uk/warranty**. Without registration, the standard pan-European 1 year warranty applies.

OKI SYSTEMS (UK) LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 1784 274300 WWW.OKI.CO.UK

WARNING! This product complies with EN55022 Class B. However, when fitted with the optional scanner and/or finisher, compliance to EN55022 is Class A. In a domestic environment this configuration may cause radio interference, in which case the user may be required to take adequate measures.

